

American Electric Power

4010 Inbound 864 Implementation Guide

VERSION: 1.0

Author: AEP B2B Technologies Group

864

Text Message

Functional Group=TX

This Draft Standard for Trial Use contains the format and establishes the data content of the Text Message Transaction Set (864) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide users with a capability to electronically move messages, contracts, explanations, and other one-time communications. It is the intent of this transaction set to provide electronic communication (messages) for people, not for computer processing. The use of the transaction set to transmit quasi or unique transaction set standards is discouraged. The use of the Text Message transaction set demands of the sender certain detailed information about the recipient. The transaction set's purpose is to provide communication to the recipient in some human-readable form. The recipient's network will dictate what capabilities are available for delivery of the information. It is the responsibility of the sender to obtain this information and include it in the transmission.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BMG	Beginning Segment For Text Message	M	1			Must use
030	DTM	Date/Time Reference	O	10			Used
LOOP ID - N1					200		
040	N1	Name	O	1			Used
080	REF	Reference Identification	O	12			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - MIT					>1		
010	MIT	Message Identification	M	1			Must use
080	MSG	Message Text	M	100000			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	SE	Transaction Set Trailer	M	1			Must use

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set	M	ID	3/3	Must use
		Code Name 864 Text Message				
ST02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BMG Beginning Segment For Text Message

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 3

User Option (Usage): Must use

To indicate the beginning of a Text Message Transaction Set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BMG01	353	Transaction Set Purpose Code Description: Code identifying purpose of transaction set	M	ID	2/2	Must use
		<u>Code</u> <u>Name</u>				
		00 Original				
BMG02	352	Description Description: A free-form description to clarify the related data elements and their content	O	AN	1/80	Used
BMG03	640	Transaction Type Code Description: Code specifying the type of transaction	O	ID	2/2	Used
		<u>Code</u> <u>Name</u>				
		03 Report Message				

Comments:

1. BMG02 contains the message subject.

DTM Date/Time Reference

Pos: 030	Max: 10
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier Description: Code specifying type of date or time, or both date and time	M	ID	3/3	Must use
		Code Name				
		009 Process				
DTM02	373	Date Description: Date expressed as CCYYMMDD	X	DT	8/8	Used
DTM03	337	Time Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	X	TM	4/8	Used
DTM04	623	Time Code Description: Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	O	ID	2/2	Used
		Code Name				
		CS Central Standard Time				

Syntax:

1. R020305 - At least one of DTM02,DTM03,DTM05 is required
2. C0403 - If DTM04 is present, then all of DTM03 are required
3. P0506 - If either DTM05,DTM06 is present, then all are required

Loop N1

Pos: 040	Repeat: 200
Optional	
Loop: N1	Elements: N/A

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
040	N1	Name	O	1		Used
080	REF	Reference Identification	O	12		Used

N1**Name**

Pos: 040	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual	M	ID	2/3	Must use
		Code Name				
		FR Message From				
		TO Message To				
N102	93	Name Description: Free-form name	X	AN	1/60	Used
N103	66	Identification Code Qualifier Description: Code designating the system/method of code structure used for Identification Code (67)	X	ID	1/2	Used
		Code Name				
		12 Telephone Number (Phone)				
		92 Assigned by Buyer or Buyer's Agent				
N104	67	Identification Code Description: Code identifying a party or other code	X	AN	2/80	Used

Syntax:

1. R0203 - At least one of N102,N103 is required
2. P0304 - If either N103,N104 is present, then all are required

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

REF Reference Identification

Pos: 080	Max: 12
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier Description: Code qualifying the Reference Identification	M	ID	2/3	Must use
		Code Name				
		VR Vendor ID Number				
REF02	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN	1/30	Used

Syntax:

1. R0203 - At least one of REF02,REF03 is required

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop MIT

Pos: 010	Repeat: >1
Mandatory	
Loop: MIT	Elements: N/A

To identify the beginning of a specific message and to allow the identification of a subject for the message

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	MIT	Message Identification	M	1		Must use
080	MSG	Message Text	M	100000		Must use

MIT**Message Identification**

Pos: 010	Max: 1
Detail - Mandatory	
Loop: MIT	Elements: 2

User Option (Usage): Must use

To identify the beginning of a specific message and to allow the identification of a subject for the message

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MIT01	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN	1/30	Must use
MIT02	352	Description Description: A free-form description to clarify the related data elements and their content	O	AN	1/80	Used

Semantics:

1. MIT01 contains the message number.
2. MIT02 contains the message subject.

Comments:

1. MIT03 default is 80 characters.
2. MIT04 default is 66 lines.

MSG Message Text

Pos: 080	Max: 100000
Detail - Mandatory	
Loop: MIT	Elements: 1

User Option (Usage): Must use

To provide a free-form format that allows the transmission of text information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-Form Message Text Description: Free-form message text	M	AN	1/264	Must use

Syntax:

1. C0302 - If MSG03 is present, then all of MSG02 are required

Semantics:

1. MSG03 is the number of lines to advance before printing.

Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

SE Transaction Set Trailer

Pos: 010	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments Description: Total number of segments included in a transaction set including ST and SE segments	M	N0	1/10	Must use
SE02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Comments:

1. SE is the last segment of each transaction set.